



IR Vandal Proof Day & Night Dome Camera

KCC-IRSD400

Function

- KCC-IRSD400 : 1/3" Sony Super HAD CCD 410k
- High Resolution
- CDS Auto Switching Infrared LED
- 11 Infrared LED
- Visibility range 10m
- Vandal proof with aluminum housing

Specifications

Model no.	KCC-IRSD400	
Image Sensor device	1/3" Color Sony Super HAD CCD	
Total pixels	NTSC	811(H) x 508(V)
	PAL	795(H) x 596(V)
Effective pixels	NTSC	768(H) x 494(V)
	PAL	752(H) x 582(V)
Scanning system	2:1 Interlace	
Scanning	NTSC	Standard 525 Lines 15.734KHz(H), 59.94Hz(V)
frequency	PAL	Standard 625 Lines 15.625KHz(H), 50Hz(V)
S/N ratio	More than 48dB (AGC Off)	
Visibility range	11 Unit infrared LEDs (850nm) : 10m	
Horizontal resolution	Day	480TV Lines
	Night	520TV Lines
Shutter speed	NTSC	1/60 - 1/100,000sec
	PAL	1/50 - 1/100,000sec
Minimum illumination	more than 0.005Lux (LED on)	
Sync. system	Internal	
Video output	VBS 1.0V p-p Composite (75Ω)	
Lens mount	Fixed Board Lens (f:6.0mm@F2.0) Standard	
White balance	Auto	
Video output jack	BNC connector	
Power input jack	φ 5.5 Jack	
Power consumption	DC12V ± 2V (Max.1.7W, 4.8W with IR LED)	
Operation temperature	-10° - 50°	
Humidity	Within 90% RH	
Weight (Approx.)	0.4kg	

Picture View



Dimensions

